



A compact valve box with 4 internal solenoid valves that connect to a 24Vac controller. Installation is uncomplicated and the eZyvalve®4 provides a trouble free way to distribute water to a micro irrigation system.

Features

- Pre-assembled with no internal pipe connections.
- High strength UV stabilised materials.
- Includes cable seal and wire connectors.
- Water, dust and pest resistant.
- Textured non-slip lid with o-ring seal and stainless steel screws.
- 3/4" BSP male threaded inlet and outlet connections.

Applications

Landscape, home gardens, greenhouses and nurseries. Above and below ground installation.



eZyvalve®4

Performance	
PRESSURE (kPa)	DISCHARGE (lpm)
50	13
100	18
150	22
200	25
250	28
300	31
350	34

eZyvalve®4

TYPE	ORDER CODE	PACK QUANTITY	PACKS PER CARTON	CARTON (kg)
eZyvalve®4 - Valve Box 4 Solenoid Valves 3/4" BSPM 24Vac	16605	1	10	10.1



Braided Hose

Accessories

TYPE	ORDER CODE	PACK QUANTITY	PACKS PER CARTON	CARTON (kg)
BRAIDED HOSE 1000 mm x 3/4" BSPF	90603	1	40	16.1
TAP ADAPTOR 1" BSPF x 3/4" BSPM	45825	25	30	12.0



eZyvalve®4 with Braided hose

Specifications

DIMENSIONS PACKAGED	CONNECTION TYPE
LENGTH 105 mm	Inlet: 3/4" BSPM tapered
DEPTH 182 mm	Outlet: 3/4" BSPM parallel x 4
WIDTH 182 mm	
WEIGHT (approx) 1075 g	

OPERATING SPECIFICATIONS	
FLOW	1 L/min - 30 L/min
PRESSURE	20 kPa - 1250 kPa
AMBIENT TEMPERATURE	2°C - 60°C
ELECTRICAL	24Vac, inrush current 320 mA, holding current 260 mA at 50 Hz